Hydrotech

# 89 Series Water Softener

## **The Trouble With Hard Water**

Hard water (calcium & magnesium) is a common problem for many homeowners and businesses. When hardness minerals are combined with heat it forms troublesome scale. Scale causes costly build-up in your plumbing, water heater and other water using appliances. When combined with soap, the minerals form soap curd or scum that makes skin dry and itchy, hair lifeless, laundry dull and builds up on fixtures.



# A System That Pays For Itself

Hydrotech offers the highest efficiency at the best price! Save 7,500 lbs of salt, 125,000 gal. water and \$2,750 in operating costs!\*



\* Based on expected 15 year life. \$6.00 per 40 Lb bag of salt. \$2.76 per cubic yard of water.

### **Benefit From Softer Water:**

- Silky shiny hair, Soft supple skin
- Use up to 75% less soap
- Lower water heating cost by 29%
- Save as much as \$479 annually\*
  - \*Potential savings based on Water Quality
    Research Foundation Battelle Institute Study








**Cabinet Model** 

#### **Options:**

- Traditional twin tank or cabinet style
- Round or square brine tanks in black, blue or vanilla
- Pressure tanks in black, blue or natural
- Tank jackets with black caps in chrome, grey, blue or vanilla

#### **Features:**

- True 1" porting provides high flow rates for larger homes
- Upflow Regeneration with Optimal Precision Brining provides high-efficiency performance and lowest possible salt usage.
- Adjustable backwash frequency saves up to 2,000 gallons of water per year
- Description Large 4 line Touch Pad LCD display. No confusing symbols or codes.
- Automatic reserve adjusts based on actual usage
- Automatic System Flush refreshes system during periods of non use preventing bacteria growth
- Soft Water Recharge performs quick regeneration ensuring you never run out of soft water
- Soft Water Brine Tank Refill conserves capacity and keeps brine tank clean
- Time saving quick connect features on bypass, drain line and powercord
- Meter immediate; meter delayed; meter override; vacation and calendar clock modes
- Self charging capacitor keeps date / time of day for 48 hours while programming remains in permanent memory
- Space saving bypass with integrated turbine meter
- Comes with 1" straight NPT
- Seven Year Control Valve Warranty, Lifetime Warranty on Tanks



Upflow Regeneration drives the hardness minerals up through the already depleted resin and out to drain - saving both salt and the unused portion of the resin for future use.





Year Warranty Lifetime Warrant Control Valve Pressure tank

| Model       | System Capacity Grains |  |                   | Flow Rate        |                   | Regeneration Water Usage (Gallons) |       | Mineral   | Resin   | Brine Tank /                              | Salt Capacity    | Ship            |
|-------------|------------------------|--|-------------------|------------------|-------------------|------------------------------------|-------|-----------|---------|---|------------------|-----------------|
|             | @ 10 lbs/<br>cu ft     | @ 6 lbs/<br>cu ft (Factory<br>Setting) | @ 3 lbs/<br>cu ft | Service<br>USGPM | Backwash<br>USGPM | Clean Water<br>(Factory Setting)   |       | Tank Size | Cu. Ft. | Cabinet Size Inches                       | (Lbs)            | Weight<br>(Lbs) |
| HT89UF-75   | 22,500                 | 18,750                                 | 11,250            | 10.4             | 1.5               | 34.0                               | 49.6  | 8 x 44    | 0.75    | BTS 15.0 <sup>2</sup> x34.7/BTR 18.1x34.7 | BTS 230 /BTR 270 | 93              |
| HT89UF-100  | 30,000                 | 25,000                                 | 15,000            | 11.0             | 2.0               | 43.4                               | 64.3  | 9 x 48    | 1.00    | BTS 15.0 <sup>2</sup> x34.7/BTR 18.1x34.7 | BTS 230 /BTR 270 | 110             |
| HT89UF-150  | 45,000                 | 37,500                                 | 22,500            | 11.2             | 2.4               | 62.7                               | 90.3  | 10 x 54   | 1.50    | BTS 15.0 <sup>2</sup> x34.7/BTR 18.1x34.7 | BTS 230 /BTR 270 | 141             |
| HT89UF-200  | 60,000                 | 50,000                                 | 30,000            | 12.2             | 3.5               | 87.1                               | 124.6 | 12 x 52   | 2.00    | 20.3 x 37.4                               | 385              | 158             |
| HT89UF-250  | 75,000                 | 62,500                                 | 37,500            | 15.0             | 4.0               | 108.9                              | 155.8 | 13 X 54   | 2.50    | 20.3 x 37.4                               | 385              | 198             |
| HT89UF-300  | 90,000                 | 75,000                                 | 45,000            | 12.6             | 5.0               | 139.2                              | 196.2 | 14 x 65   | 3.00    | 23.0 x 40.5                               | 550              | 244             |
| HT89UF-75C  | 22,500                 | 18,750                                 | 11,250            | 11.6             | 2.0               | 40.5                               | 56.1  | 9 x 35    | 0.75    | 13.8 x 23.6 x 43.3                        | 225              | 93              |
| HT89UF-100C | 30,000                 | 25,000                                 | 15,000            | 12.0             | 2.4               | 48.6                               | 69.5  | 10 x 35   | 1.00    | 13.8 x 23.6 x 43.3                        | 225              | 110             |

| Model       | System Capacity Grains |  |                   | Flow Rate        |                   | Regeneration Water<br>Usage (Gallons) |                  | Mineral | Resin   | Brine Tank / Cabinet Size                 | Salt Capacity    | Ship            |
|-------------|------------------------|--|-------------------|------------------|-------------------|---------------------------------------|------------------|---------|---------|---|------------------|-----------------|
|             | @ 10 lbs/<br>cu ft     | @ 6 lbs/<br>cu ft (Factory<br>Setting) | @ 3 lbs/<br>cu ft | Service<br>USGPM | Backwash<br>USGPM | Clean Water<br>(Factory Setting)      | Problem<br>Water |         | Cu. Ft. | Inches                                    | (Lbs)            | Weight<br>(Lbs) |
| HT89DF-75   | 22,500                 | 18,750                                 | 11,250            | 10.4             | 1.5               | 34.0                                  | 49.6             | 8 x 44  | 0.75    | BTS 15.0 <sup>2</sup> x34.7/BTR 18.1x34.7 | BTS 230 /BTR 270 | 93              |
| HT89DF-100  | 30,000                 | 25,000                                 | 15,000            | 11.0             | 2.0               | 43.4                                  | 64.3             | 9 x 48  | 1.00    | BTS 15.0 <sup>2</sup> x34.7/BTR 18.1x34.7 | BTS 230 /BTR 270 | 110             |
| HT89DF-150  | 45,000                 | 37,500                                 | 22,500            | 11.2             | 2.4               | 62.7                                  | 90.3             | 10 x 54 | 1.50    | BTS 15.0 <sup>2</sup> x34.7/BTR 18.1x34.7 | BTS 230 /BTR 270 | 141             |
| HT89DF-200  | 60,000                 | 50,000                                 | 30,000            | 12.2             | 3.5               | 87.1                                  | 124.6            | 12 x 52 | 2.00    | 20.3 x 37.4                               | 385              | 158             |
| HT89DF-250  | 75,000                 | 62,500                                 | 37,500            | 15.0             | 4.0               | 108.9                                 | 155.8            | 13 X 54 | 2.50    | 20.3 x 37.4                               | 385              | 198             |
| HT89DF-300  | 90,000                 | 75,000                                 | 45,000            | 12.6             | 5.0               | 139.2                                 | 196.2            | 14 x 65 | 3.00    | 23.0 x 40.5                               | 550              | 244             |
| HT89DF-75C  | 22,500                 | 18,750                                 | 11,250            | 11.6             | 2.0               | 40.5                                  | 56.1             | 9 x 35  | 0.75    | 13.8 x 23.6 x 43.3                        | 225              | 93              |
| HT89DF-100C | 30,000                 | 25,000                                 | 15,000            | 12.0             | 2.4               | 48.6                                  | 69.5             | 10 x 35 | 1.00    | 13.8 x 23.6 x 43.3                        | 225              | 110             |



Canature

WaterGroup

In the U.S.A. 1-877-288-9888 In Canada 1-877-288-9888 www.hydrotechwater.com Your Local Water Treatment Professional